

M A T E R I A L S A F E T Y D A T A S H E E T

2K OLIVE DRAB # 8 TM9

MANUFACTURER: SIERRA CORP/TK PRODUCTS EMERGENCY PHONE: 1-800-424-9300
ADDRESS : 11400 WEST 47TH STREET INFORMATION PHONE: (952)938-7223
MINNETONKA, MN 55343

DATE PRINTED : 12/22/2008 NAME OF PREPARER : Safety Director
REVISION DATE :

SECTION 1 - PRODUCT IDENTIFICATION

PRODUCT NAME: 2K OLIVE DRAB # 8 TM9 HMIS CODES: H F R P
PRODUCT CODE: .11034 2 3 0 G

SECTION 2 - COMPOSITION/INGREDIENT INFORMATION

Table with columns: COMPONENT, CAS NUMBER, WEIGHT PERCENT, OSHA PEL, ACGIH TLV, OTHER. Lists ingredients like Butyl Acetate, Xylene, Toluene, etc.

- * Chemical(s) that are chronic health hazards. Refer to section 3 for further information.
+ Toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
^ Hazardous Air Pollutant established by the EPA as directed by the Clean Air Act of 1990.
Chemical(s) which may be considered a cancer hazard by IARC and/or NTP. Refer to section 11 for further information.

SECTION 3 - HEALTH HAZARDS IDENTIFICATION

PRIMARY ROUTES OF EXPOSURE:
Skin contact, eye contact, and inhalation.

EFFECTS OF ACUTE EXPOSURE:
EYES: Contact with eyes may cause irritation including burning, watering, and redness.
SKIN: Contact may cause mild skin irritation including redness, burning, and drying and cracking of skin. Continued exp may develop into dermatitis. Solvents can penetrate the skin and cause systematic effects similar to those under inhalation symptoms.

INHALATION: High vapor concentrations are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, asthma, drowsiness, unconsciousness, and other central nervous system effects, and possibly death.

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Small amounts aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury.

CHRONIC HEALTH EFFECTS:
Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage (Sometimes referred to as Solvent or Painter's Syndrome). Intentional misuse by deliberately concentrating and inhaling this material may be harmful or fatal. Chronic exposure may also cause damage to the respiratory system, lungs, eyes, skin, gastrointestinal tract, liver, spleen and kidneys. Repeated skin contact may cause persistent irritation or dermatitis.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Conditions aggravated by exposure may include skin disorders, respiratory (asthma-like) disorders, and pre-existing liver or kidney conditions.

SECTION 4 - FIRST AID MEASURES

IF ON SKIN: Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use. If irritation develops and persists, seek medical attention.

exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

VENTILATION:

If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, electrical systems safe for such locations must be used.

PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing gloves impervious to solvents and other appropriate protective clothing. Launder contaminated clothing before reuse.

EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.

===== SECTION 9 - PHYSICAL/CHEMICAL PROPERTIES =====

PHYSICAL STATE: Liquid

COLOR: Various colors

ODOR: Hydrocarbon odor

SOLUBILITY IN WATER: Insoluble/Negligible

SPECIFIC GRAVITY (H2O=1): 1.1

VAPOR DENSITY: Heavier than air.

BOILING RANGE: 171 F - 302 F

EVAPORATION RATE: Faster than nBuAc Equal to nBuAc

COATING V.O.C.: 543 g/l (4.53 lb/gal)

===== SECTION 10 - STABILITY/REACTIVITY DATA =====**STABILITY:**

Stable under normal conditions and handling.

CONDITIONS TO AVOID:

All possible sources of ignition.

INCOMPATIBILITY (MATERIALS TO AVOID):

Avoid exposure to strong oxidizing agents and reducing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, carbon monoxide, various oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION:

Will not occur.

===== SECTION 11 - TOXICOLOGICAL INFORMATION =====**SENSITIZATION:**

None known.

CARCINOGENICITY:

The indicated chemical(s) is listed by ICGIH, NTP, or OSHA as a known human carcinogen (See section 2). IARC concluded that there is "sufficient evidence in experimental animals for the carcinogenicity of carbon black" and inadequate evidence of carcinogenicity in humans, and overall evaluated carbon black as a "possible carcinogen to humans" (Group 2B). Carbon black has not been listed as a carcinogen by NTP or OSHA. Because this product is a free flowing liquid, inhalation is not an expected route of exposure.

REPRODUCTIVE TOXICITY:

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

TERATOGENICITY (BIRTH DEFECTS):

Yes. 2,4 Pentanedione may cause congenital malformation in the fetus. Available information indicates that Toluene is NOT teratogenic, but it can be toxic to the embryo and fetus and may reduce fertility. In animal tests, high inhaled doses of Toluene has caused reduced litter sizes, retarded development of the fetus, and increased incidence of non-lethal abnormalities.

MUTAGENICITY:

Yes. 2,4 Pentanedione is a possible mutagen.

===== SECTION 12 - ECOLOGICAL INFORMATION =====**ENVIRONMENTAL DATA:**

Although no information is available for this specific product mixture, individual components may by themselves may have ecological affects.

===== SECTION 13 - DISPOSAL CONSIDERATIONS =====

This product is considered a RCRA hazardous waste due to the characteristic(s) of D001 (ignitability). Waste is subject to the land disposal restrictions in 40 CFR 268.40 and may require treatment standards. Consult state and local regulations to determine whether they are more stringent than the federal requirements.

Container contents should be completely used and containers empty prior to discarding. Container rinsate could be considered a RCRA hazardous waste and must be discarded in compliance with all applicable regulations. Larger empty containers, such as drums, should be returned to a professional drum reconditioner. To assure proper disposal of smaller empty containers, consult with state and local regulations and disposal authorities.

===== SECTION 14 - REGULATORY INFORMATION =====

SHIPPING NAME:

UN1263, Paint, 3, III

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory.

This product does contain a chemical(s) subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372). See section 2.

STATE SPECIFIC REQUIREMENTS:

This product contains a chemical(s) known to the state of California to cause cancer, birth defects or reproductive harm, which are subject to the requirements of California Proposition 65.

Contains trace amounts of Formaldehyde.

2,4 Pentanedione - Birth defects.

Toluene - Reproductive harm.

STATE LISTED COMPONENTS	CAS NUMBER	STATE CODE
Xylene	1330-20-7	CA, CT, FL, IT, LA, MA, ME, MN, PA, RI
Ethyl Benzene	100-41-4	CA, NJ, PA

===== DISCLAIMER =====

The information contained within this MSDS was obtained from sources which Sierra/TK Products believe are reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding it's accuracy or correctness. We do not assume responsibility for loss, damage or expense arising from storage, use, or disposal of this product.

CONDITIONS OF SALE/LIMITED WARRANTY: Sierra/TK Products, warrants that this product conforms to the label descriptions, is free from manufacturing defects, and is fit for the ordinary purposes for which such goods are used. Inasmuch as the use of this product by others and other factors affecting product performance are beyond Sierra/TK Products' control, Sierra/TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular pupose. Should this product fail to give satisfactory results, Sierra/TK Products will replace the product or, at its option, refund the purchase price. This is the sole and exclusive remedy for any failure of this product to perform as warranted and shall also constitute liquidated damages in case of loss. Under no curcumstances shall the buyer be entitled to any other remedy or damages. Remedies for incidental and consequential damages are specifically excluded. Sierra/TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of this product unless specifically authorized by Sierra/TK Products in writing.